

PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	WITHOUT PLUG
FA11671	COPPER	26 AMPS	55 AMPS
FA11671-02	MOLYBDENUM	26 AMPS	28 AMPS
FA11671-03	NICKEL	16.5 AMPS	16.5 AMPS
FA11671-04	304 STN STL	3.6 AMPS	3.6 AMPS


RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-55°C TO 125°C	-269° TO 450°C

MATES WITH POWERPLUG FP10884-02

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

THREE 10KV FEEDTHROUGHS



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/15/2006
A1	MH	08/24/2006	MPST0041-0ST		ENG APPR.	MH	08/24/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA11671SL REV. A1