


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA14467	COPPER	55 AMPS
FA14467-02	MOLYBDENUM	28 AMPS
FA14467-03	NICKEL	16.5 AMPS
FA14467-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	12KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25° TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWELVE 12KV FEEDTHROUGHS



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/28/2006
A1	MH	08/28/2006	FTST0034-1ST		ENG APPR.	MH	08/28/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA14467SL REV. A1