


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA10701	COPPER	55 AMPS
FA10701-02	MOLYBDENUM	28 AMPS
FA10701-03	NICKEL	16.5 AMPS
FA10701-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	14KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269° TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

14KV FEEDTHROUGH

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006
B1	MH	04/28/2006	FTST0005-0ST		ENG APPR.	MH	04/28/2006

PART NO. (SEE TABLE) REV. B



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10701SL REV. B1