

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11403	COPPER	185 AMPS
FA11403-03	NICKEL	56 AMPS
FA11403-04	304 STN STL	12 AMPS


RATINGS	
VOLTAGE:	20KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-80°C TO 450°C*

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

20KV FLUTED FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006
A1	MH	03/21/2006	FTFL0006-ST		ENG APPR.	MH	03/21/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA11403SL REV. A1