


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA14577	COPPER	100 AMPS
FA14577-02	MOLYBDENUM	50 AMPS
FA14577-03	NICKEL	30 AMPS
FA14577-04	304 STN STL	6.5 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25° TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

5KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/28/2006
A1	MH	08/28/2006	FTST0051-1ST		ENG APPR.	MH	08/28/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA14577SL REV. A1