



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA14941	COPPER	330 AMPS
FA14941-03	NICKEL	98 AMPS
FA14941-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25° TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8 KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/29/2006
A1	MH	08/29/2006	FTCL0044-3ST		ENG APPR.	MH	08/29/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA14941SL REV. A1